

MODEL	1E5(♣)	4♣	5♣	6♣	8♣	MODEL	2E5(♣)	4♣	5♣	6♣	8♣
		HERMETIC R-12						HERMETIC R-22			
NET OIL PRESSURE		75	75	75	75	NET OIL PRESSURE		75	75	75	75
CYLINDERS		4	5	6	8	CYLINDERS		4	5	6	8
BORE		3.66	3.66	3.66	3.66	BORE		3.66	3.66	3.66	3.66
STROKE		2-3/4	2-3/4	2-3/4	2-3/4	STROKE		2-3/4	2-3/4	2-3/4	2-3/4
DISPLACEMENT CFM		117.2	146.5	175.8	234.4	DISPLACEMENT CFM		117.2	146.5	175.8	234.4
OIL GRADE		300	300	300	300	OIL GRADE		300	300	300	300
OIL CHARGE PINTS		32	34	34	36	OIL CHARGE PINTS		32	34	34	36
NET WEIGHT		1290	1415	1444	1616	NET WEIGHT		1298	1406	1444	1704
RATED TONS	R-12	30	40	50	60	RATED TONS	R-22	50	60	75	100
								LARGE MOTOR BARREL (18-1/2")			
MOTOR SIZE HP		30	40	50	60	MOTOR SIZE HP		50	60	75	100
ELECTRICAL DATA		A/C AIR COOLED - W/C WATER COOLED				ELECTRICAL DATA		A/C AIR COOLED - W/C WATER COOLED			
230-3-60	LRA	456	614	750	910	230-3-60	LRA	750	910	1100	1520
	A/C RLA	96	130	155	191		A/C RLA	155	191	248	266
	W/C RLA	88	114	133	170		W/C RLA	133	170	202	310
460-3-60	LRA	228	307	375	455	460-3-60	LRA	375	455	550	760
	A/C RLA	48	65	78	96		A/C RLA	78	96	124	155
	W/C RLA	44	57	67	85		W/C RLA	67	85	101	133
575-3-60	LRA	168	226	274	333	575-3-60	LRA	274	333	400	555
	A/C RLA	41	55	65	80		A/C RLA	65	80	101	131
	W/C RLA	36	48	56	72		W/C RLA	56	72	86	113