

MODEL	LAC0310	LAH0310	LAL0310	LAM0310	NRB0310	NRD0310	NRN0310	NRB0400	NRA0500	NRL0500	NRM0500	
NET OIL PRESSURE	N/A	N/A	N/A	N/A	20-60	20-60	20-60	20-60	20-60	20-60	20-60	
CYLINDERS	2	2	2	2	2	2	2	2	2	2	2	
BORE	2-7/16	2-1/4	2-3/8	2-7/16	2-1/4	2-7/16	2-3/16	2-1/2	2-7/16	2-7/16	2-3/16	
STROKE	1-7/16	1-7/16	1-7/16	1-11/16	1-7/16	1-7/16	2-1/8	1-7/16	1-7/16	2-1/8	2-1/8	
DISPLACEMENT CFH	815	698	775	952	698	815	970	698	815	1208	970	
OIL GRADE	150	150	150	150	150	150	150	150	150	150	150	
OIL CHARGE OZ.	96	96	96	96	80	80	80	80	80	80	80	
NET WEIGHT	210	210	210	210	216	216	216	231	231	236	231	
RATED BTUH @ SST LISTED	R12 45°F		31700			30500				M		
	R12 0°F	13300	11200	12700		8500	12850					
	R12 -20°F				7840			9200		57500		
	R22 45°F								50200	35730	44000	
	R22 25°F								30500		E	
R502-20°F	11600	9000				11600					23600	
MOTOR SIZE HP	3	3	3	3	3	3	3	4	5	5	5	
ELECTRICAL DATA												
230 -1- 60	LRA	86.0	86.0	86.0	86.0	84.0	84.0	84.0	131.0	131.0	131.0	131.0
	RLA	15.4	15.1	14.2	12.7	18.1	21.1	17.7	32.9	34.3	36.5	36.5
	MCC	21.5	21.1	19.9	17.7	25.3	28.9	24.8	46.1	48.0	FRN-50	49.2
208-230 -3- 60	LRA	82.0	82.0	82.0	82.0	82.0	82.0	82.0	141.0	141.0	141.0	141.0
	RLA	10.0	10.7	10.9	10.0	12.9	14.3	13.0	21.8	19.2	24.3	24.3
	MCC	12.9	15.0	15.3	14.0	18.1	18.0	18.2	30.6	26.9	FRN-35	30.8
460 -3- 60	LRA	41.0	41.0	41.0	41.0	41.0	41.0	41.0	62.5	62.5	62.5	62.5
	RLA	5.7	5.7	5.0	4.7	6.4	7.3	6.5	11.3	9.6	12.1	12.1
	MCC	8.0	8.0	7.0	6.6	9.0	10.1	9.1	15.8	13.5	FRS-17.5	15.4

Conditions: 130° Condensing Temperature, 0° Subcooling, 65° RGT,