

MODEL	155	157	205	216	207	208	255	266	257	258	259
	DLFN	DCN	DCFN	DLFN	DHN	DCN	DHF/N	DCFN	DLFN	DHN	DCN
NET OIL PRESSURE	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50
CYLINDERS	3	4	3	4	4	4	3	4	4	4	4
BORE	3-1/8	3-1/8	3-1/8	3-1/8	3-1/8	3-1/8	3-1/8	3-1/8	3-1/8	3-1/8	3-9/16
STROKE	2-3/8	2-3/8	2-3/8	2	2-3/8	2-3/4	2-3/8	2	2-3/8	2-3/4	2-3/8
DISPLACEMENT CFM	55.3	73.8	55.3	62.1	73.8	85.4	55.3	62.1	73.8	85.4	96.0
OIL GRADE	150	150	150	150	300	150	300	150	150	300	150
OIL CHARGE PINTS	19	19	19	19	19	19	19	19	19	19	19
NET WEIGHT	590	590	590	590	600	600	590	590	600	600	600
RATED BTUH X 1000	R-12 45°F				263.0					306.0	
	R-12 10°F		113.0			131.0					147.0
	R-22 45°F						319.0				
	R-22 10°F			132.0				163.0			
	R-502 -25°F	52.0			56.0				69.0		
MOTOR SIZE HP											

Conditions: R-12 & R-502, 0° Subcooling, 65° RGT, 115° SCT. R22, 10° Subcooling, 25° Superheat, 115° SCT.

MODEL	307	308	309	311	316	357	358	359	361	408	409
	DCFN	DLFN	DHN	DCN	DHF/N	DHF/N	DCFN	DLFN	DHN	DHF/N	DCFN
NET OIL PRESSURE	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50	30-50
CYLINDERS	4	4	4	4	4	4	4	4	4	4	4
BORE	3-1/8	3-1/8	3-9/16	3-9/16	3-1/8	3-1/8	3-1/8	3-9/16	3-9/16	3-1/8	3-9/16
STROKE	2-3/8	2-3/4	2-3/8	2-3/4	2	2-3/8	2-3/4	2-3/8	2-3/4	2-3/4	2-3/8
DISPLACEMENT CFM	73.8	85.4	96.0	111.0	62.1	73.8	85.4	96.0	111.0	85.4	96.0
OIL GRADE	150	150	300	150	300	300	150	150	300	300	150
OIL CHARGE PINTS	19	19	19	19	19	19	19	19	19	19	19
NET WEIGHT	600	600	600	600	590	600	600	600	600	600	600
RATED BTUH X 1000	R-12 45°F		343.0						397.0		
	R-12 10°F			175.0							
	R-22 45°F				371.0	433.0				500.0	
	R-22 10°F	183.0					211.0				237.0
	R-502 -25°F		80.0					91.0			
MOTOR SIZE HP											

Conditions: R-12 & R-502, 0° Subcooling, 65° RGT, 115° SCT. R22, 10° Subcooling, 25° Superheat, 115° SCT.

MODEL	411	509	511	511
	DLFN	DHFN	DCFN	DHF/N
NET OIL PRESSURE	30-50	30-50	30-50	30-50
CYLINDERS	4	4	4	4
BORE	3-9/16	3-9/16	3-9/16	3-9/16
STROKE	2-3/4	2-3/8	2-3/4	2-3/4
DISPLACEMENT CFM	111.0	96.0	111.0	111.0
OIL GRADE	150	300	150	300
OIL CHARGE PINTS	19	19	19	19
NET WEIGHT	600	600	600	600
RATED BTUH X 1000	R-12 45°F			
	R-12 10°F			
	R-22 45°F		551.0	649.0
	R-22 10°F			283.0
	R-502 -25°F	107.0		
MOTOR SIZE HP				

Conditions: R-12 & R-502, 0° Subcooling, 65° RGT, 115° SCT. R22, 10° Subcooling, 25° Superheat, 115° SCT.