

<b>MODEL</b>	<b>M</b>	<b>3</b>	<b>0</b>	<b>D</b>	<b>-</b>	<b>2</b>	<b>E</b>	<b>4</b>	<b>A</b>	<b>-</b>	<b>A</b>
--------------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

<b>DIGIT</b>	<b>1</b>	<b>2 &amp; 3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>	<b>9</b>
--------------	----------	------------------	----------	----------	----------	----------	----------	----------

COMPRESSOR TYPE

NOMINAL SIZE	
10	10 TON
15	15 TON
20	20 TON
25	25 TON
30	30 TON

ELECTRICAL CHARACTERISTICS	
C	200/60/3
D	230/60/3
E	460/60/3
F	575/60/3
G	230/60/3
H	397/50/3
M	230/460/60/3

DESIGN SEQUENCE

SOLENOID VOLTAGE	
A	115 VAC
B	230 VAC

NUMBER OF CYLINDERS THAT UNLOAD

TYPE UNLOADING  
E = ELECTRIC SOLENOID ON CYLINDER HEAD

NUMBER OF CYLINDERS 3, 4, 5, 6 OR 8