

| MODEL | CRHR | 260 | 261* | 320 | 321* | 350 | 351* | 380 | 381* | 400 | 401* | 500 | 501* | 600 | 601* |
|------------------|---------|-----------------------------------|-------|-------|-------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| NET OIL PRESSURE | | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 | 30 |
| CYLINDERS | | 4 | 4 | 6 | 6 | 4 | 4 | 6 | 6 | 4 | 4 | 6 | 6 | 6 | 6 |
| BORE | | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 | 3.44 |
| STROKE | | 2.75 | 2.75 | 2.3 | 2.3 | 2.3 | 2.3 | 2.75 | 2.75 | 2.75 | 2.75 | 2.3 | 2.3 | 2.75 | 2.75 |
| DISPLACEMENT CFM | | 103.5 | 103.5 | 129.9 | 129.9 | 86.6 | 86.6 | 155.3 | 155.3 | 103.5 | 103.5 | 129.9 | 129.9 | 155.3 | 155.3 |
| OIL GRADE | | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 | 150 |
| OIL CHARGE PINTS | | 20 | 20 | 27 | 27 | 20 | 20 | 27 | 27 | 20 | 20 | 27 | 27 | 27 | 27 |
| NET WEIGHT | | 815 | 815 | 950 | 950 | 815 | 815 | 977 | 977 | 815 | 815 | 950 | 950 | 977 | 977 |
| RATED TONS | R-12 | 26 | 26 | 32 | 32 | | | 38 | 38 | | | | | | |
| | R-500 | | | | | | | | | | | | | | |
| | R-22 | | | | | 35 | 35 | | | 40 | 40 | 50 | 50 | 60 | 60 |
| | R-502 | | | | | X | X | | | X | X | X | X | X | X |
| MOTOR SIZE HP | | | | | | 35 | 35 | | | 40 | 40 | 50 | 50 | 60 | 60 |
| ELECTRICAL DATA | | A/C AIR COOLED - W/C WATER COOLED | | | | | | | | | | | | | |
| 200-3-60 | LRA | 485 | 485 | 582 | 582 | 729 | 729 | 725 | 725 | 910 | 910 | 910 | 910 | 990 | 990 |
| | A/C RLA | 103 | 103 | 125 | 125 | 201 | 201 | 140 | 140 | 258 | 258 | 258 | 258 | 316 | 316 |
| | W/C RLA | | | | | 164 | 164 | 128 | 128 | 234 | 234 | 234 | 234 | 280 | 280 |
| 230-3-60 | LRA | 420 | 420 | 506 | 506 | 631 | 631 | 630 | 630 | 792 | 792 | 792 | 792 | 860 | 860 |
| | A/C RLA | 90 | 90 | 109 | 109 | 171 | 171 | 122 | 122 | 226 | 226 | 226 | 226 | 275 | 275 |
| | W/C RLA | | | | | 149 | 149 | 95 | 95 | 212 | 212 | 212 | 212 | 252 | 252 |
| 460-3-60 | LRA | 210 | 210 | 253 | 253 | 315 | 315 | 315 | 315 | 396 | 396 | 396 | 396 | 430 | 430 |
| | A/C RLA | 45 | 45 | 55 | 55 | 88 | 88 | 61 | 61 | 113 | 113 | 113 | 113 | 138 | 138 |
| | W/C RLA | | | | | 74 | 74 | 55 | 55 | 106 | 106 | 106 | 106 | 126 | 126 |

* Low Lift Valves - Required Below 10⁰ F