

Z B 6 W 2 - E 46 / 50 S

Z 6 W 2 B - E 46 S

ADDITIONAL VOLTAGE CODE IF PRESENT

COMPRESSOR SERIES

NUMBER OF CYLINDERS - 4, 6

MOTOR VENDOR
L = LEROY SOMER
S = A. O. SMITH

DISPLACEMENT		
H	4 Cyl., 2.7" Bore, 2.4" Stroke	56.03 CFM
J	4 Cyl., 2.9" Bore, 2.4" Stroke	64.45 CFM
K	4 Cyl., 2.7" Bore, 3" Stroke	70.03 CFM
M	4 Cyl., 2.9" Bore, 3" Stroke	80.56 CFM
N	6 Cyl., 2.7" Bore, 2.4" Stroke	84.04 CFM
R	6 Cyl., 2.9" Bore, 2.4" Stroke	96.67 CFM
S	6 Cyl., 2.7" Bore, 3" Stroke	105.04 CFM
W	6 Cyl., 2.9" Bore, 3" Stroke	120.84 CFM
AE	6 Cyl., 3.1" Bore, 3" Stroke	141.21 CFM

VOLTAGE CODE	
17 = 200-3-60	58 = 575-3-60
28 = 230-3-60	59 = 190-3-50
40 = 380-3-60	63 = 220-3-50
43 = 440-3-50	64 = 346-3-50
46 = 460-3-60	70 = 500-3-50
50 = 380/415-3-50	

MOTOR SIZE (A, B, C, D, or E)	
A = 25 HP	D = 55 HP
B = 35 HP	E = 65 HP
C = 45 HP	

NO. OF STEPS OF UNLOADING

STYLE A, B